

Basic plotting and matrix operations (Octave)

June 21, 2017

1 Table of Contents

- 1 Quick demonstration of GNU Octave
 - 1.1 Some basic plotting
 - 1.2 Some basic linear algebra
 - 1.3 3D plotting

2 Quick demonstration of GNU Octave

In a Jupyter Notebook

- This [Jupyter Notebook](#) was written by [Lilian Besson](#).
- It uses the unofficial [Octave kernel for Jupyter](#) by [\[@Calysto\]\(https://github.com/calysto/\)](#).

2.1 Some basic plotting


```
In [1]: % Some variables
N = 100
disp(['Number of values N =', num2str(N)])
h = 1 / N
disp(['Step h = ', num2str(h)])
```

```
N = 100
Number of values N =100
h = 0.010000
Step h = 0.01
```


```
In [2]: % Some arrays
t = 0 : h : 2*pi;
x = cos(t);
y = sin(t);
length(t)
length(x)
length(y)
```

```
ans = 629
ans = 629
ans = 629
```

```
In [3]: fig = figure();
        plot(t, x, 'r*-')
        grid on
        hold on
        plot(t, y, 'b+-')
        legend(['\cos(t)', '\sin(t)'])
        title('Cosinus and sinus on [0, 2 \pi]')
        % whitebg(fig);
```



```
In [4]: fig = figure();
        grid on
        plot(x, y)
        title('\sin(t) as function of \cos(t)')
        % whitebg(fig);
```



2.2 Some basic linear algebra

In [5]: `a = [[1 0 1]; [0 1 1]; [1 1 0]]`

a =

```
1 0 1
0 1 1
1 1 0
```

In [6]: `a'`

ans =

```
1 0 1
0 1 1
1 1 0
```

```
In [7]: b = 1 + a^5
```

```
b =
```

```
12  11  12
11  12  12
12  12  11
```

eig gives the eigen values:

```
In [8]: l_a = eig(a)
        l_b = eig(b)
```

```
l_a =
```

```
-1.00000
 1.00000
 2.00000
```

```
l_b =
```

```
-1.00000
 1.00000
35.00000
```

```
In [9]: [Ua, Sa, Va] = svd(a)
        [Ub, Sb, Vb] = svd(b)
```

```
Ua =
```

```
-5.7735e-01  4.0825e-01 -7.0711e-01
-5.7735e-01 -8.1650e-01 -7.8505e-17
-5.7735e-01  4.0825e-01  7.0711e-01
```

```
Sa =
```

Diagonal Matrix

```
2.00000    0    0
 0  1.00000    0
 0    0  1.00000
```

```
Va =
```

```
-0.57735  0.81650 -0.00000
```

```
-0.57735 -0.40825 0.70711
-0.57735 -0.40825 -0.70711
```

Ub =

```
-5.7735e-01 4.0825e-01 -7.0711e-01
-5.7735e-01 -8.1650e-01 -1.6098e-15
-5.7735e-01 4.0825e-01 7.0711e-01
```

Sb =

Diagonal Matrix

```
35.00000 0 0
0 1.00000 0
0 0 1.00000
```


Vb =

```
-0.57735 0.81650 -0.00000
-0.57735 -0.40825 0.70711
-0.57735 -0.40825 -0.70711
```


2.3 3D plotting

Some basic 3D plotting:


```
In [10]: x = linspace(-2, 2, 50);
y = linspace(-2, 2, 50);
[xx,yy] = meshgrid(x, y);
mesh(xx, yy, 4 - (xx.^2 + yy.^2))
```




```
In [11]: x = linspace(-2, 2, 50);  
         y = linspace(-2, 2, 50);  
         [xx,yy] = meshgrid(x, y);  
         meshc(xx, yy, 4 - (xx.^2 + yy.^2))
```



```
In [13]: # From https://octave.sourceforge.io/octave/function/plot3.html
z = [0:0.05:5];
plot3(cos (2*pi*z), sin (2*pi*z), z, ";helix;");
plot3(z, exp (2i*pi*z), ";complex sinusoid;");
```



```
In [14]: clf;  
z = [0:0.05:5];  
plot3 (cos (2*pi*z), sin (2*pi*z), z);  
legend ("helix");  
title ("plot3() of a helix");
```

```
In [15]: clf;
          colormap ("default");
          [X, Y] = meshgrid (linspace (-3, 3, 40));
          Z = sqrt (abs (X .* Y)) ./ (1 + X.^2 + Y.^2);
          meshc (X, Y, Z);
          title ("meshc() combines mesh/contour plots");
```