

A Recipe for the Semantics of Reversible Programming

Louis LEMONNIER

University of Edinburgh



THE UNIVERSITY *of* EDINBURGH
informatics

LoVe seminar, LIPN. 7th November 2024

Reversible Programming


Originally

- Landauer and Bennett, 1961: Reversible Computation and Energy Dissipation.
- Reversible programs: for a program t , there is t^{-1} such that $t; t^{-1} = \text{skip}$.
- Applications to quantum computing.


What we do

- Reversibility, but **not totality**.
- Syntax for reversible functions.
- With enough expressivity.
- Through the categorical semantics.

Backward determinism



Forward determinism



[Kaarsgaard&Rennela21]

A general framework: dagger categories

Origine: functional analysis where $\langle fx | y \rangle = \langle x | f^\dagger y \rangle$.

Category \mathbf{C} equipped with a functor $(-)^{\dagger} : \mathbf{C}^{\text{op}} \rightarrow \mathbf{C}$, such that:

- On objects, $A^{\dagger} = A$.
- On morphisms:
 - $(g \circ f)^{\dagger} = f^{\dagger} \circ g^{\dagger}$,
 - $f^{\dagger \dagger} = f$.

Example with partial injective functions between sets, here $\{0, 1\}$.

$$\text{not: } \begin{array}{ccc} 0 & \xrightarrow{\quad} & 0 \\ 1 & \xrightarrow{\quad} & 1 \end{array} \quad g: \begin{array}{ccc} 0 & \xrightarrow{\quad} & 0 \\ 1 & \xrightarrow{\quad} & 1 \end{array} \quad g^{\dagger}: \begin{array}{ccc} 0 & \xrightarrow{\quad} & 0 \\ 1 & \xrightarrow{\quad} & 1 \end{array}$$

A very important class of morphisms: *partial \dagger -isomorphism*. $ff^{\dagger} = f$.

Examples of relevant dagger categories

Sets and bijections.




Examples of relevant dagger categories

Sets and bijections.



Sets and partial injections.



g is undefined on 1.

Examples of relevant dagger categories

Sets and bijections. $\begin{array}{ccc} 0 & \xrightarrow{\quad} & 0 \\ 1 & \xrightarrow{\quad} & 1 \end{array}$

Sets and partial injections. $g: \begin{array}{ccc} 0 & \xrightarrow{\quad} & 0 \\ 1 & \xrightarrow{\quad} & 1 \end{array}$ g is undefined on 1.

Hilbert spaces and unitary maps. $\begin{array}{ccc} |0\rangle & \longrightarrow & |+\rangle \\ |1\rangle & \longrightarrow & |-\rangle \end{array}$ where

$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix} \quad |+\rangle = \begin{bmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{bmatrix} \quad |-\rangle = \begin{bmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{bmatrix}$$

Examples of relevant dagger categories

Sets and bijections. $\begin{array}{ccc} 0 & \xrightarrow{\quad} & 0 \\ 1 & \xrightarrow{\quad} & 1 \end{array}$

Sets and partial injections. $g: \begin{array}{ccc} 0 & \xrightarrow{\quad} & 0 \\ 1 & \xrightarrow{\quad} & 1 \end{array}$ g is undefined on 1.

Hilbert spaces and unitary maps. $\begin{array}{ccc} |0\rangle & \longrightarrow & |+\rangle \\ |1\rangle & \longrightarrow & |-\rangle \end{array}$ where

$$|0\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix} \quad |1\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix} \quad |+\rangle = \begin{bmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{bmatrix} \quad |-\rangle = \begin{bmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{bmatrix}$$

Hilbert spaces and contractions. $h: \begin{array}{ccc} |0\rangle & \longrightarrow & |+\rangle \\ |1\rangle & \longrightarrow & |-\rangle \end{array}$ $h|1\rangle = 0$.

How do you extract syntax from dagger categories?

———— Cartesian closed category ————

How do you extract syntax from dagger categories?

———— Cartesian closed category ————

- Cartesian product \times .

How do you extract syntax from dagger categories?

———— Cartesian closed category ————

- Cartesian product \times .
 - ◆ Type $A \times B$.

How do you extract syntax from dagger categories?

———— Cartesian closed category ————

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.

How do you extract syntax from dagger categories?

———— Cartesian closed category ————

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .

How do you extract syntax from dagger categories?

———— Cartesian closed category ————

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.

How do you extract syntax from dagger categories?

———— Cartesian closed category ————

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

How do you extract syntax from dagger categories?

———— Cartesian closed category ———— ————— Dagger category —————

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

How do you extract syntax from dagger categories?

Cartesian closed category

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

Dagger category

- Not cartesian, but often monoidal.

How do you extract syntax from dagger categories?

Cartesian closed category

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

Dagger category

- Not cartesian, but often monoidal.
 - ◆ Type $A \otimes B$.

How do you extract syntax from dagger categories?

Cartesian closed category

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

Dagger category

- Not cartesian, but often monoidal.
 - ◆ Type $A \otimes B$.
 - ◆ Linear type system.

How do you extract syntax from dagger categories?

Cartesian closed category

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

Dagger category

- Not cartesian, but often monoidal.
 - ◆ Type $A \otimes B$.
 - ◆ Linear type system.
- Not monoidal closed.

How do you extract syntax from dagger categories?

Cartesian closed category

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

Dagger category

- Not cartesian, but often monoidal.
 - ◆ Type $A \otimes B$.
 - ◆ Linear type system.
- Not monoidal closed.
 - ◆ No **ground** function type.

How do you extract syntax from dagger categories?

Cartesian closed category

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

Dagger category

- Not cartesian, but often monoidal.
 - ◆ Type $A \otimes B$.
 - ◆ Linear type system.
- Not monoidal closed.
 - ◆ No **ground** function type.
 - ◆ Is there a way to form functions?

How do you extract syntax from dagger categories?

Cartesian closed category

- Cartesian product \times .
 - ◆ Type $A \times B$.
 - ◆ Constructor $\langle t_1, t_2 \rangle$.
- Right adjoint to the tensor \rightarrow .
 - ◆ Type $A \rightarrow B$.
 - ◆ Constructor $\lambda x.t$.

Dagger category

- Not cartesian, but often monoidal.
 - ◆ Type $A \otimes B$.
 - ◆ Linear type system.
- Not monoidal closed.
 - ◆ No **ground** function type.
 - ◆ Is there a way to form functions?

Hopefully, there is **another** way.

Our new functions

We can **cheat** with our partial inverse!

Our new functions

We can **cheat** with our partial inverse!

$$\begin{aligned} \llbracket \Delta \vdash t : A \rrbracket & : \llbracket \Delta \rrbracket \rightarrow \llbracket A \rrbracket \\ \llbracket \Delta \vdash t : A \rrbracket^\dagger & : \llbracket A \rrbracket \rightarrow \llbracket \Delta \rrbracket \end{aligned}$$

Our new functions

We can **cheat** with our partial inverse!

$$\begin{aligned} \llbracket \Delta \vdash t : A \rrbracket & : \llbracket \Delta \rrbracket \rightarrow \llbracket A \rrbracket \\ \llbracket \Delta \vdash t : A \rrbracket^\dagger & : \llbracket A \rrbracket \rightarrow \llbracket \Delta \rrbracket \end{aligned}$$

What do we do with this?

Our new functions

We can **cheat** with our partial inverse!

$$\begin{aligned} \llbracket \Delta \vdash t : A \rrbracket & : \llbracket \Delta \rrbracket \rightarrow \llbracket A \rrbracket \\ \llbracket \Delta \vdash t : A \rrbracket^\dagger & : \llbracket A \rrbracket \rightarrow \llbracket \Delta \rrbracket \end{aligned}$$

What do we do with this?

Given $\Delta \vdash t : A$ $\Delta \vdash t' : B$

We form a function $t \mapsto t' : A \leftrightarrow B$, Whose semantics is

Our new functions

We can **cheat** with our partial inverse!

$$\begin{aligned} \llbracket \Delta \vdash t : A \rrbracket & : \llbracket \Delta \rrbracket \rightarrow \llbracket A \rrbracket \\ \llbracket \Delta \vdash t : A \rrbracket^\dagger & : \llbracket A \rrbracket \rightarrow \llbracket \Delta \rrbracket \end{aligned}$$

What do we do with this?

Given $\Delta \vdash t : A$ $\Delta \vdash t' : B$

We form a function $t \mapsto t' : A \leftrightarrow B$, Whose semantics is

$$\llbracket A \rrbracket \xrightarrow{\llbracket \Delta \vdash t : A \rrbracket^\dagger} \llbracket \Delta \rrbracket \xrightarrow{\llbracket \Delta \vdash t' : B \rrbracket} \llbracket B \rrbracket$$

Our new functions

We can **cheat** with our partial inverse!

$$\begin{aligned} \llbracket \Delta \vdash t : A \rrbracket & : \llbracket \Delta \rrbracket \rightarrow \llbracket A \rrbracket \\ \llbracket \Delta \vdash t : A \rrbracket^\dagger & : \llbracket A \rrbracket \rightarrow \llbracket \Delta \rrbracket \end{aligned}$$

What do we do with this?

Given $\Delta \vdash t : A$ $\Delta \vdash t' : B$

We form a function $t \mapsto t' : A \leftrightarrow B$, Whose semantics is

$$\llbracket A \rrbracket \xrightarrow{\llbracket \Delta \vdash t : A \rrbracket^\dagger} \llbracket \Delta \rrbracket \xrightarrow{\llbracket \Delta \vdash t' : B \rrbracket} \llbracket B \rrbracket$$

This is a **reversible** function! We have $(t \mapsto t')^{-1} = t' \mapsto t$, whose semantics is:

Our new functions

We can **cheat** with our partial inverse!

$$\begin{aligned} \llbracket \Delta \vdash t : A \rrbracket & : \llbracket \Delta \rrbracket \rightarrow \llbracket A \rrbracket \\ \llbracket \Delta \vdash t : A \rrbracket^\dagger & : \llbracket A \rrbracket \rightarrow \llbracket \Delta \rrbracket \end{aligned}$$

What do we do with this?

Given $\Delta \vdash t : A$ $\Delta \vdash t' : B$

We form a function $t \mapsto t' : A \leftrightarrow B$, Whose semantics is

$$\llbracket A \rrbracket \xrightarrow{\llbracket \Delta \vdash t : A \rrbracket^\dagger} \llbracket \Delta \rrbracket \xrightarrow{\llbracket \Delta \vdash t' : B \rrbracket} \llbracket B \rrbracket$$

This is a **reversible** function! We have $(t \mapsto t')^{-1} = t' \mapsto t$, whose semantics is:

$$\llbracket B \rrbracket \xrightarrow{\llbracket \Delta \vdash t' : B \rrbracket^\dagger} \llbracket \Delta \rrbracket \xrightarrow{\llbracket \Delta \vdash t : A \rrbracket} \llbracket A \rrbracket$$

Together with pattern-matching

With a sum type \oplus :

$$\frac{\Delta \vdash t: A}{\Delta \vdash \text{inj}_l t: A \oplus B}$$

$$\frac{\Delta \vdash t: B}{\Delta \vdash \text{inj}_r t: A \oplus B}$$

Together with pattern-matching

With a sum type \oplus :

$$\frac{\Delta \vdash t: A}{\Delta \vdash \text{inj}_l t: A \oplus B} \quad \frac{\Delta \vdash t: B}{\Delta \vdash \text{inj}_r t: A \oplus B}$$

We introduce **orthogonality** (to ensure reversibility):

Together with pattern-matching

With a sum type \oplus :

$$\frac{\Delta \vdash t: A}{\Delta \vdash \text{inj}_l t: A \oplus B} \quad \frac{\Delta \vdash t: B}{\Delta \vdash \text{inj}_r t: A \oplus B}$$

We introduce **orthogonality** (to ensure reversibility):

$$\frac{}{\text{inj}_l t_1 \perp \text{inj}_r t_2} \quad \frac{t_1 \perp t_2}{C[t_1] \perp C[t_2]} \quad \text{with } \begin{cases} \llbracket t_1 \rrbracket^\dagger \circ \llbracket t_1 \rrbracket = \text{id} \\ \llbracket t_1 \rrbracket^\dagger \circ \llbracket t_2 \rrbracket = 0 \end{cases} \quad \text{when } t_1 \perp t_2$$

Together with pattern-matching

With a sum type \oplus :

$$\frac{\Delta \vdash t: A}{\Delta \vdash \text{inj}_l t: A \oplus B} \quad \frac{\Delta \vdash t: B}{\Delta \vdash \text{inj}_r t: A \oplus B}$$

We introduce **orthogonality** (to ensure reversibility):

$$\frac{}{\text{inj}_l t_1 \perp \text{inj}_r t_2} \quad \frac{t_1 \perp t_2}{C[t_1] \perp C[t_2]} \quad \text{with } \begin{cases} \llbracket t_1 \rrbracket^\dagger \circ \llbracket t_1 \rrbracket = \text{id} \\ \llbracket t_1 \rrbracket^\dagger \circ \llbracket t_2 \rrbracket = 0 \end{cases} \quad \text{when } t_1 \perp t_2$$

Our functions are then:

$$\left\{ \begin{array}{l} t_1 \mapsto t'_1 \\ t_2 \mapsto t'_2 \\ \vdots \\ t_m \mapsto t'_m \end{array} \right\} : A \leftrightarrow B$$

whenever $\Delta_i \vdash t_i: A$ and $t_j \perp t_k$, $\Delta_i \vdash t'_i: B$ and $t'_j \perp t'_k$.

Example and semantics

$$\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A$$

Denotational semantics:

Example and semantics

$$\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A$$

Denotational semantics:

$$\left[\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A \right] = \left(\begin{array}{c} [A] \\ [B] \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \begin{array}{c} [B] \\ [A] \end{array} \right) + \left(\begin{array}{c} [A] \\ [B] \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \begin{array}{c} [B] \\ [A] \end{array} \right)$$

Operational semantics:

Example and semantics

$$\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A$$

Denotational semantics:

$$\left[\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A \right] = \left(\begin{array}{c} [A] \\ [B] \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \begin{array}{c} [B] \\ [A] \end{array} \right) + \left(\begin{array}{c} [A] \\ [B] \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \begin{array}{c} [B] \\ [A] \end{array} \right)$$

Operational semantics:

$$\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r x \mapsto \text{inj}_l x \end{array} \right\} \text{inj}_r v \rightarrow$$

Example and semantics

$$\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A$$

Denotational semantics:

$$\left[\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A \right] = \left(\begin{array}{c} [A] \\ [B] \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \begin{array}{c} [B] \\ [A] \end{array} \right) + \left(\begin{array}{c} [A] \\ [B] \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \begin{array}{c} [B] \\ [A] \end{array} \right)$$

Operational semantics:

$$\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r x \mapsto \text{inj}_l x \end{array} \right\} \text{inj}_r v \rightarrow (\text{inj}_l x)[v/x] \rightarrow$$

Example and semantics

$$\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A$$

Denotational semantics:

$$\left[\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r y \mapsto \text{inj}_l y \end{array} \right\} : A \oplus B \leftrightarrow B \oplus A \right] = \left(\begin{array}{c} [A] \\ [B] \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \begin{array}{c} [B] \\ [A] \end{array} \right) + \left(\begin{array}{c} [A] \\ [B] \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \begin{array}{c} [B] \\ [A] \end{array} \right)$$

Operational semantics:

$$\left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_r x \\ \text{inj}_r x \mapsto \text{inj}_l x \end{array} \right\} \text{inj}_r v \rightarrow (\text{inj}_l x)[v/x] \rightarrow \text{inj}_l v$$

The mathematical recipe /'iɛs.i.pi/

Our category \mathbf{C} such that:

The mathematical recipe /'ɪɛs.i.pi/

Our category \mathbf{C} such that:

- Inverse category.
 - ◆ Partial inverse $(-)^{\dagger}$.

The mathematical recipe /'ɪɛs.i.pi/

Our category \mathbf{C} such that:

- Inverse category.
 - ◆ Partial inverse $(-)^{\dagger}$.
 - ◆ Takes care of pattern-matching.

The mathematical recipe /'ɪɛs.i.pi/'

Our category \mathbf{C} such that:

- Inverse category.
 - ◆ Partial inverse $(-)^{\dagger}$.
 - ◆ Takes care of pattern-matching.
- Rig structure.
 - ◆ Usual monoidal product \otimes .

The mathematical recipe /'ɪɛs.i.pi/'

Our category \mathbf{C} such that:

- Inverse category.
 - ◆ Partial inverse $(-)^{\dagger}$.
 - ◆ Takes care of pattern-matching.
- Rig structure.
 - ◆ Usual monoidal product \otimes .
 - ◆ **Disjointness** tensor \oplus with jointly epic injections.

The mathematical recipe /'ɪɛs.i.pi/

Our category \mathbf{C} such that:

- Inverse category.
 - ◆ Partial inverse $(-)^{\dagger}$.
 - ◆ Takes care of pattern-matching.
- Rig structure.
 - ◆ Usual monoidal product \otimes .
 - ◆ **Disjointness** tensor \oplus with jointly epic injections.
- Join structure.
 - ◆ **Compatible** morphisms on their domain and codomain admit a join.

The mathematical recipe /'ɪɛs.i.pi/

Our category \mathbf{C} such that:

- Inverse category.
 - ◆ Partial inverse $(-)^{\dagger}$.
 - ◆ Takes care of pattern-matching.
- Rig structure.
 - ◆ Usual monoidal product \otimes .
 - ◆ **Disjointness** tensor \oplus with jointly epic injections.
- Join structure.
 - ◆ **Compatible** morphisms on their domain and codomain admit a join.
 - ◆ Sometimes, provides a nice structure on morphisms.

Examples:

- Sets and partial injective functions **Pinj**.
- Hilbert spaces and contractions **Contr** (sometimes written **Hilb**_{≤1}).

The case of inverse categories (such as \mathbf{PInj})

To Infinity and Beyond

Some reading: [Axelsen&Kaarsgaard16] + [Fiore04] + some calculations.

→ A suitable inverse category **C**

To Infinity and Beyond

Some reading: [Axelsen&Kaarsgaard16] + [Fiore04] + some calculations.

→ A suitable inverse category \mathbf{C} is **parameterised DCPO-algebraically ω -compact**.

To Infinity and Beyond

Some reading: [Axelsen&Kaarsgaard16] + [Fiore04] + some calculations.

→ A suitable inverse category \mathbf{C} can model infinite data types $\mu X.A$.

To Infinity and Beyond

Some reading: [Axelsen&Kaarsgaard16] + [Fiore04] + some calculations.

→ A suitable inverse category \mathbf{C} can model infinite data types $\mu X.A$.

Examples:

$$\text{Nat} = \mu X.1 \oplus X$$

To Infinity and Beyond

Some reading: [Axelsen&Kaarsgaard16] + [Fiore04] + some calculations.

→ A suitable inverse category \mathbf{C} can model infinite data types $\mu X.A$.

Examples:

$$\text{Nat} = \mu X.1 \oplus X \quad [A] = \mu X.1 \oplus (A \otimes X)$$

And we want to parse those infinite types:

To Infinity and Beyond

Some reading: [Axelsen&Kaarsgaard16] + [Fiore04] + some calculations.

→ A suitable inverse category \mathbf{C} can model infinite data types $\mu X.A$.

Examples:

$$\text{Nat} = \mu X.1 \oplus X \quad [A] = \mu X.1 \oplus (A \otimes X)$$

And we want to parse those infinite types:

$$\text{map}(\omega) = \text{fix } f. \left\{ \begin{array}{l} [] \mapsto [] \\ h :: t \mapsto (\omega h) :: (f t) \end{array} \right\} : [A] \leftrightarrow [B]$$

To Infinity and Beyond

Some reading: [Axelsen&Kaarsgaard16] + [Fiore04] + some calculations.

→ A suitable inverse category \mathbf{C} can model infinite data types $\mu X.A$.

Examples:

$$\text{Nat} = \mu X.1 \oplus X \quad [A] = \mu X.1 \oplus (A \otimes X)$$

And we want to parse those infinite types:

$$\text{map}(\omega) = \text{fix } f. \left\{ \begin{array}{l} [] \mapsto [] \\ h :: t \mapsto (\omega h) :: (f t) \end{array} \right\} : [A] \leftrightarrow [B]$$

Works in inverse categories thanks to **DCPO-enrichment**: $g \leq f$ defined as $fg^\dagger g = g$.

To Infinity and Beyond

Some reading: [Axelsen&Kaarsgaard16] + [Fiore04] + some calculations.

→ A suitable inverse category \mathbf{C} can model infinite data types $\mu X.A$.

Examples:

$$\text{Nat} = \mu X.1 \oplus X \quad [A] = \mu X.1 \oplus (A \otimes X)$$

And we want to parse those infinite types:

$$\text{map}(\omega) = \text{fix } f. \left\{ \begin{array}{l} [] \mapsto [] \\ h :: t \mapsto (\omega h) :: (f t) \end{array} \right\} : [A] \leftrightarrow [B]$$

Works in inverse categories thanks to **DCPO-enrichment**: $g \leq f$ defined as $fg^\dagger g = g$.

$$\text{fix}(F) = \sup_n \{F^n(\perp)\}$$

Summary of the language (mandatory slide)

(Ground types) $A, B ::= I \mid A \oplus B \mid A \otimes B \mid$

(Function types) $T_1, T_2 ::= A \leftrightarrow B \mid$

(Unit term) $t, t_1, t_2 ::= *$

(Pairing) $\mid t_1 \otimes t_2$

(Injections) $\mid \text{inj}_l t \mid \text{inj}_r t$

(Function application) $\mid \omega t$

(Abstraction) $\omega ::= \{t_1 \mapsto t'_1 \mid \dots \mid t_m \mapsto t'_m\}$

Summary of the language (mandatory slide)

(Ground types)	A, B	$::=$	$I \mid A \oplus B \mid A \otimes B \mid X \mid \mu X.A$
(Function types)	T_1, T_2	$::=$	$A \leftrightarrow B$
(Unit term)	t, t_1, t_2	$::=$	$*$
(Pairing)			$\mid t_1 \otimes t_2$
(Injections)			$\mid \text{inj}_l t \mid \text{inj}_r t$
(Function application)			$\mid \omega t$
(Inductive terms)			$\mid \text{fold } t$
(Abstraction)	ω	$::=$	$\{t_1 \mapsto t'_1 \mid \dots \mid t_m \mapsto t'_m\}$
(Fixed points)			$\mid f \mid \text{fix } f.\omega$

Summary of the language (mandatory slide)

(Ground types)	A, B	$::=$	$I \mid A \oplus B \mid A \otimes B \mid X \mid \mu X.A$
(Function types)	T_1, T_2	$::=$	$A \leftrightarrow B \mid T_1 \rightarrow T_2$
(Unit term)	t, t_1, t_2	$::=$	$*$
(Pairing)			$\mid t_1 \otimes t_2$
(Injections)			$\mid \text{inj}_l t \mid \text{inj}_r t$
(Function application)			$\mid \omega t$
(Inductive terms)			$\mid \text{fold } t$
(Abstraction)	ω	$::=$	$\{t_1 \mapsto t'_1 \mid \dots \mid t_m \mapsto t'_m\}$
(Fixed points)			$\mid f \mid \text{fix } f.\omega$
(Higher abstractions)			$\mid \lambda f.\omega \mid \omega_2 \omega_1$

λ -calculus thanks to **DCPO**-enrichment.

The language is **Turing complete!** (even if it is reversible)

The language is **Turing complete!** (even if it is reversible)



← ask this guy (Kostia Chardonnet, currently works in Nancy)

The language is **Turing complete!** (even if it is reversible)



← ask this guy (Kostia Chardonnet, currently works in Nancy)

————— Roughly —————

- Reversible Turing Machines [Axelsen&Glück11].
 - ◆ Simulate your favourite Turing machines.
- Encode RTMs in our language:
 - ◆ Alphabet & states mapped to $I \oplus \dots \oplus I$.
 - ◆ Tape as lists.
 - ◆ Functions simulating one-step transition of δ .
 - ◆ Iterate until final state.

A variety of diverging functions

Usual

$$\text{fix } f^T . f^T : T$$

A variety of diverging functions

Usual

$$\text{fix } f^T . f^T : T$$

Less usual

$$\text{fix } f^{A \leftrightarrow B} . \{x \mapsto f x\} : A \leftrightarrow B$$

A variety of diverging functions

Usual

$$\text{fix } f^T . f^T : T$$

Less usual

$$\text{fix } f^{A \leftrightarrow B} . \{x \mapsto f x\} : A \leftrightarrow B$$

$$\begin{aligned} (\text{fix } f . \{x \mapsto f x\}) v &\rightarrow \{x \mapsto (\text{fix } f . \{x \mapsto f x\}) x\} v \\ &\rightarrow ((\text{fix } f . \{x \mapsto f x\}) x)[v/x] \\ &= (\text{fix } f . \{x \mapsto f x\}) v \end{aligned}$$

A variety of diverging functions

Usual

$$\text{fix } f^T . f^T : T$$

Less usual

$$\text{fix } f^{A \leftrightarrow B} . \{x \mapsto f x\} : A \leftrightarrow B$$

$$\begin{aligned} (\text{fix } f . \{x \mapsto f x\}) v &\rightarrow \{x \mapsto (\text{fix } f . \{x \mapsto f x\}) x\} v \\ &\rightarrow ((\text{fix } f . \{x \mapsto f x\}) x)[v/x] \\ &= (\text{fix } f . \{x \mapsto f x\}) v \end{aligned}$$

New challenger

A variety of diverging functions

Usual

$$\text{fix } f^T . f^T : T$$

Less usual

$$\text{fix } f^{A \leftrightarrow B} . \{x \mapsto f x\} : A \leftrightarrow B$$

$$\begin{aligned} (\text{fix } f . \{x \mapsto f x\}) v &\rightarrow \{x \mapsto (\text{fix } f . \{x \mapsto f x\}) x\} v \\ &\rightarrow ((\text{fix } f . \{x \mapsto f x\}) x)[v/x] \\ &= (\text{fix } f . \{x \mapsto f x\}) v \end{aligned}$$

New challenger

$$\lambda g^{A_1 \leftrightarrow B_1} . \text{fix } f^{A_2 \leftrightarrow B_2} . \left\{ \begin{array}{l} \text{inj}_l x \mapsto \text{inj}_l (g x) \\ \text{inj}_r y \mapsto \text{inj}_r (f y) \end{array} \right\} : A_1 \oplus A_2 \leftrightarrow B_1 \oplus B_2$$

The (pure) quantum case

The quantum troubles

Contr (Hilbert spaces and contractive linear maps) is not enriched in an **interesting** way.

Is there a better category?

The quantum troubles

Contr (Hilbert spaces and contractive linear maps) is not enriched in an **interesting** way.

Is there a better category? I don't know.

The quantum troubles

Contr (Hilbert spaces and contractive linear maps) is not enriched in an **interesting** way.

Is there a better category? I don't know.

Can we find a way to mimic the story we have for classical reversibility?

The quantum troubles

Contr (Hilbert spaces and contractive linear maps) is not enriched in an **interesting** way.
Is there a better category? I don't know.

Can we find a way to mimic the story we have for classical reversibility?
A kind of solution with techniques adapted from **guarded recursion**.

Computation in the topos of trees

Objects in the topos of trees are cochains in **Set**:

$$X(0) \xleftarrow{r_0} X(1) \xleftarrow{r_1} X(2) \xleftarrow{\quad} \dots$$

There is a functor $L: \mathbf{Set}^{\mathbb{N}^{\text{op}}} \rightarrow \mathbf{Set}^{\mathbb{N}^{\text{op}}}$, such that LX is:

$$1 \xleftarrow{!} X(0) \xleftarrow{r_0} X(1) \xleftarrow{r_1} X(2) \xleftarrow{\quad} \dots$$

and a natural transformation $\nu: \text{id} \Rightarrow L$, such that ν_X is:

$$\begin{array}{ccccccc} X(0) & \xleftarrow{r_0} & X(1) & \xleftarrow{r_1} & X(2) & \xleftarrow{r_2} & X(3) \xleftarrow{\quad} \dots \\ \downarrow ! & & \downarrow r_0 & & \downarrow r_1 & & \downarrow r_2 \\ 1 & \xleftarrow{!} & X(0) & \xleftarrow{r_0} & X(1) & \xleftarrow{r_1} & X(2) \xleftarrow{\quad} \dots \end{array}$$

and a family of morphisms $\text{fix}_X: [LX \rightarrow X] \rightarrow X$.

A guarded category

Start with a dagger category \mathbf{C} .

Consider the category whose objects are cochains in \mathbf{C} :

$$X(0) \longleftarrow X(1) \longleftarrow X(2) \longleftarrow \dots$$

And morphisms are natural transformations in \mathbf{C} :

$$\begin{array}{ccccccc} X(0) & \longleftarrow & X(1) & \longleftarrow & X(2) & \longleftarrow & \dots \\ \downarrow & & \downarrow & & \downarrow & & \\ Y(0) & \longleftarrow & Y(1) & \longleftarrow & Y(2) & \longleftarrow & \dots \end{array}$$

This category is enriched in the topos of trees $\mathbf{Set}^{\mathbb{N}^{\text{op}}}$ (with its fixed point operator).

Some mild conditions for guarded recursion

Guarded recursion enforces termination.

Some mild conditions for guarded recursion

Guarded recursion enforces termination.

It also enforces to *advance* in the depth of the terms.

Some mild conditions for guarded recursion

Guarded recursion enforces termination.

It also enforces to *advance* in the depth of the terms.

The size of the output cannot be smaller than the size of the input (and vice versa).

Some mild conditions for guarded recursion

Guarded recursion enforces termination.

It also enforces to *advance* in the depth of the terms.

The size of the output cannot be smaller than the size of the input (and vice versa).

It still allows for the `map` function.

$$\text{map}(\omega) = \text{fix } f. \left\{ \begin{array}{l} [] \mapsto [] \\ h :: t \mapsto (\omega h) :: (f t) \end{array} \right\} : [A] \leftrightarrow [B]$$

Back to Hilbert spaces

Once we have this diagram in **Contr**:

$$\begin{array}{ccccccc} X(0) & \longleftarrow & X(1) & \longleftarrow & X(2) & \longleftarrow & \dots \\ \downarrow & & \downarrow & & \downarrow & & \\ Y(0) & \longleftarrow & Y(1) & \longleftarrow & Y(2) & \longleftarrow & \dots \end{array}$$

Back to Hilbert spaces

Once we have this diagram in **Contr**:

$$\begin{array}{ccccccc} X(0) & \longleftarrow & X(1) & \longleftarrow & X(2) & \longleftarrow & \dots \\ \downarrow & & \downarrow & & \downarrow & & \\ Y(0) & \longleftarrow & Y(1) & \longleftarrow & Y(2) & \longleftarrow & \dots \end{array}$$

We can take the limit of both cochains.

$$\begin{array}{cccccccc} X(0) & \longleftarrow & X(1) & \longleftarrow & X(2) & \longleftarrow & \dots & \longleftarrow & X_\infty \\ \downarrow & & \downarrow & & \downarrow & & & & \downarrow \\ Y(0) & \longleftarrow & Y(1) & \longleftarrow & Y(2) & \longleftarrow & \dots & \longleftarrow & Y_\infty \end{array}$$

Back to Hilbert spaces

Once we have this diagram in **Contr**:

$$\begin{array}{ccccccc} X(0) & \longleftarrow & X(1) & \longleftarrow & X(2) & \longleftarrow & \dots \\ \downarrow & & \downarrow & & \downarrow & & \\ Y(0) & \longleftarrow & Y(1) & \longleftarrow & Y(2) & \longleftarrow & \dots \end{array}$$

We can take the limit of both cochains.

$$\begin{array}{cccccccc} X(0) & \longleftarrow & X(1) & \longleftarrow & X(2) & \longleftarrow & \dots & \longleftarrow & X_\infty \\ \downarrow & & \downarrow & & \downarrow & & & & \downarrow \\ Y(0) & \longleftarrow & Y(1) & \longleftarrow & Y(2) & \longleftarrow & \dots & \longleftarrow & Y_\infty \end{array}$$

But we lose the enrichment (and therefore the nice calculus that we could have on top).

Conclusion

Take home message: no **cartesian closure** needed to have

Conclusion

Take home message: no **cartesian closure** needed to have functions,

Conclusion

Take home message: no **cartesian closure** needed to have functions, inductive types,

Conclusion

Take home message: no **cartesian closure** needed to have functions, inductive types, recursion.

Conclusion

Take home message: no **cartesian closure** needed to have functions, inductive types, recursion.
The situation is trickier for (pure) quantum computation.

Conclusion

Take home message: no **cartesian closure** needed to have functions, inductive types, recursion.
The situation is trickier for (pure) quantum computation.

Thank you!